

Installation Instructions

STAR 2 LED CEILING LAMP

CODE# 1415

Rated Voltage 220-240V~ 50Hz

Thank you for purchasing this quality Zebbies product. To ensure correct function and safety, please read and follow all instructions carefully before assembly, installation and use of this product. Please keep instructions for future reference.

Installation requirements

- Must be installed by a licensed electrician.
- All wiring and installation of the light fitting must adhere to local and national wiring rules.
- Select a suitable location for installation;
 - This product is suitable for indoor use only.
 - The mounting point must support 2 times the weight of the fitting.
 - Ensure the fitting is not installed in direct line of an air vent/system.
 - When installing a fitting in an area prone to moisture, ensure that the area is well ventilated and an appropriately rated exhaust fan is used if required. Damage or corrosion caused by moisture is not a product fault, and as such is not covered under warranty.
- The fitting must not be used if the diffuser on the LED light module has been damaged or cracked.
- Take care not to pull any electrical wires during unpacking as this may damage the connection.
- Lay out all the components on a smooth surface and make sure there are no components missing before assembling. If parts are missing, return the complete product to the place of purchase for inspection or replacement.
- Check whether the fitting has been damaged during transport. Do not operate/install any product which appears damaged in any way. Return the complete product to the place of purchase for inspection, repair or replacement.
- Ensure power to the circuit you are working on has been switched OFF before commencing any electrical work.

Installation directions

NOTE: Assembly and installation of this fitting must be done by a licensed electrician.

NOTE: Due to the size/weight of the fitting, two people or more may be required to lift up the fitting during installation.

1. Remove all packaging material from the product and be careful not to throw away accessories that maybe hidden within the packaging material.
2. Remove the mounting bracket from the ceiling plate by loosening the screws on four sides. Use the mounting bracket as a template to mark the screw positions on the ceiling. Install the mounting bracket (2) onto the ceiling by using appropriately sized mounting screws (3) and anchor (1). Ensure the screws and anchors used are suitable for the mounting surface and the surrounding environment.

Installation Instructions

3. Remove the cover and connect the mains supply wire to the terminal block (4). Ensure the wires are secure and no bare wires are exposed. Install the cover back over the terminal block.

Mains Supply Wire

Earth – Yellow/Green 

Neutral – Blue or Black

Live – Brown or Red

Fitting Wire

Yellow/Green or 

Blue

Brown

4. Install the fitting onto the mounting bracket and secure by the screws (5) on four sides.
5. Refer to the drawing and hang the square glass (6) and the decorative glass beads strings (7) to the matching position.
6. Install the circular glass panel onto the LED by three flat screws (8).
7. After the installation, switch on the fitting to test all the lighting functions and enjoy your new lighting product.

CAUTION: The light source of lamp can not be replaced, please replace a whole new lamp if the light source is broken.

Safety tips

- Always ensure the power is OFF and the fitting has cooled down before performing any maintenance, cleaning or making any adjustment to the fitting.
- To avoid injury or damage to the fitting, ensure that power leads and screws are secure before connecting the power.
- Select a suitable location away from liquids and hazards.
- Ensure that the fitting does not come in contact with corrosive chemicals, etc.
- To clean, wipe with a damp clean cloth. Never soak the fitting with water.

Specifications	
CODE#	1415
Finish	Chrome
Insulation Class	Class I
Rated Voltage	220-240V~ 50Hz
Rated Wattage	60W
LED specs	5400 lumens, 4000K, Non-dimmable
Weight	7.5kg
Dimensions	DIA.600mm H:265mm

