

Please read this instruction sheet carefully and keep it for future reference. The fitting must be installed by a licensed electrician.

INSTALLATION

Before installation, ensure power is off, and please pay attention to the following steps

- Hammer the plastic anchors (6) to the ground. Feed the incoming mains cable (9) through the rubber grommet in the base and attach the base to the ground with suitable screws.
- Connect the mains supply to the terminal block (7), using the following colour code for the wiring:
- 1.) Connect the brown wire to the corresponding terminal on the terminal block Marked "L"
- 2.) Connect the blue wire to the corresponding terminal on the terminal block market "N"
- Fix terminal block cover (8) with screw
- Fix the fitting (4) with the machine screws (5).
- Install the bulb (3) to the socket (the bulb must not exceed the specified wattage on the label.) Attach the metal rack (2) and plastic global cover (1) to the fitting and rotate clock-wise until tight.
- · Restore mains supply and switch on.

MAINTENANCE OF OUTDOOR LIGHTS

BEFORE INSTALLING AN OUTDOOR LIGHT FITTING:

Ensure that all screws and movable parts are covered in Copper slip, Inox or Vaseline, this will help prevent oxidization and allow for easy maintenance of replacement bulbs.

In coastal locations the treatment must be repeated four times a year.